

Compact Track Loaders / T450 Compact Track Loader

Specifications & Options

■ Standard Optional N/A Not Applicable



Bobcat T450

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	61.1 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	1,400 lb
Operating Capacity (50% of Tip)	2000 lb
Tipping Load	4000 lb
Operating Weight	6148 lb
Travel Speed	11.7 km/h
Travel Speed (2-speed option)	17.7 km/h
Ground Pressure (Rubber)	4.7 psi

⊖ Capacities

Fuel Tank	65.5 l
-----------	--------

⊖ Hydraulic System

System Relief @ Quick Couplers	3,300 psi
Auxiliary Std Flow	63,2 l/min
Auxiliary High Flow	n/a

⊖ Dimension

Length	98.4 in
Length without Attachment	98.4 in
Length with Standard Bucket	126.6 in
Width	55 in
Width (with bucket)	56 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	109.5 in
Reach @ Maximum Height	23.5 in
Turning Radius	77.9 in
Length of track on ground	50.2 in
Track Width	11.8 in

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.