

# WDC

## WELDER GENERATORS

For on the job welding repairs at the farm or construction site, trust Wallenstein's portable welder generators.



**Helmet & 25' Welding Cable Included**



**Electric Start**

# 50% DUTY CYCLE

**50% Duty Cycle**  
5 full minutes weld time, then 5 minutes of rest time.



**Auto Idle**  
Generator switches to idle mode when no load is present.

## CHOOSE YOUR COLOR

When ordering, please use 3 letter color designation behind models



-RED

-ORA

-GRN

-BLU

-YEL

-GRY

-BLK

POWERED by  
**HONDA**™



### WDC160

**Welder Specifications**

- 160 Max. Amps

**Generator Specifications**

- 3500 Max. Watts
- 3000 Continuous Watts
- 24 Continuous Amps (120V)
- 12 Continuous Amps (240V)
- 389 CC Honda GX340 Engine
- 6.1 L Fuel Tank Capacity
- 70.5 dBA at 23'
- 4 Hours Run Time at Half Load

- 3 Hours Run Time at Full Load
- 2 x 120V 20A Outlets (2 Duplex, GFCI NEMA 5-20R)
- 1 x 120/240V 30A Outlet (Twist Lock, NEMA L14-30R)
- 2 x 15A Pop-out Breakers
- Recoil Start
- Automatic Engine Shut Down if Oil Level is Low
- Dimensions (LxWxH) 29" x 20" x 23"
- 183 lbs. Total Weight



### WDC190E

**Welder Specifications**

- 190 Max. Amps

**Generator Specifications**

- 3500 Max. Watts
- 3000 Continuous Watts
- 24 Continuous Amps (120V)
- 12 Continuous Amps (240V)
- 389 CC Honda GX390 Engine
- 6.1 L Fuel Tank Capacity
- 70.5 dBA at 23'
- 3.5 Hours Run Time at Half Load

- 2.75 Hours Run Time at Full Load
- 2 x 120V 20A Outlets (2 Duplex, GFCI NEMA 5-20R)
- 1 x 120/240V 30A Outlet (Twist Lock, NEMA L14-30R)
- 2 x 15A Pop-out Breakers
- Electric Start (Requires Z93201 Battery, Not Included)
- Automatic Engine Shut Down if Oil Level is Low
- Dimensions (LxWxH) 29" x 20" x 23"
- 197 lbs. Total Weight



### WDC190EA

**Welder Specifications**

- 190 Max. Amps

**Generator Specifications**

- 3500 Max. Watts
- 3000 Continuous Watts
- 24 Continuous Amps (120V)
- 12 Continuous Amps (240V)
- 389 CC Honda GX390 Engine
- 15.5 L Fuel Tank Capacity
- 70.5 dBA at 23'
- 12 Hours Run Time at Half Load
- 7 Hours Run Time at Full Load

- 4 x 120V 20A Outlets (2 Duplex, GFCI NEMA 5-20R)
- 1 x 120/240V 30A Outlet (Twist Lock, NEMA L14-30R)
- 2 x 15A Pop-out Breakers
- Auto Idle
- Electric Start (Requires Z93201 Battery, Not Included)
- Automatic Engine Shut Down if Oil Level is Low
- Dimensions (LxWxH) 29" x 20" x 28"
- 213 lbs. Total Weight