

8" I-BEAM DECKOVER (F8)



Lengths: 16' - 30'



*Pictured with optional 3' dovetail



Length	Axles	Est. Base Weight†
16'	2 x 7,000 lbs	3,200 lbs / 1,451 kg
18'	2 x 7,000 lbs	3,400 lbs / 1,542 kg
20'	2 x 7,000 lbs	3,600 lbs / 1,633 kg
22'	2 x 7,000 lbs	3,820 lbs / 1,733 kg
24'	2 x 7,000 lbs	4,060 lbs / 1,842 kg
26'	2 x 7,000 lbs	4,340 lbs / 1,969 kg

† Weights are estimated for base trailer.

PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (10,000 lb.)
- 2 - Dexter E- Z lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Tool Tray In Tongue
- 6' 6" Slide in Ramps w/ Holders
- 8" x 10 lb. I-Beam Tongue
- 8" x 10 lb. I-Beam Main Frame
- 3" Channel Crossmembers 16" on Center
- 2" Treated Pine Lumber Deck
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- 96" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- Amber Side Turn Flashers
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- GN Option Equipped with 2 Jacks
- GN Equipped with Lockable Front Toolbox
- GN Equipped with Chain Holder
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" Adjustable (14,000 lb.)*
- BP 2 5/16" Adjustable Rigid Mount (25,000 lb.)
- Rigid Mount Pintle Eye- Face-mount
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- GN 2 5/16" Round (25,000 lb.) w/ Toolbox
- GN 2 5/16" Square (25,000 lb.) w/ Toolbox
- BP 2 5/16" Adj. Cplr w/HD 6 hole Chn Brkt (20k)

AXLE OPTIONS

7,000# (DEXTER)

- (2) Electric (Spring)*
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (3) Electric (Spring)
- (3) Electric (Torsion)
- (3) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (3) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

8,000# OIL BATH W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Surge Hydraulic Drum [Surge Coupler] (Spring)
- (3) Electric (Spring)
- (3) Electric (Torsion)

7,000# W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)

- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (3) Electric (Spring)
- (3) Electric (Torsion)
- (3) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (3) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

8,000# OIL BATH AXLES, 235/80 LR-E TIRES (DEXTER)

- (2) Electric (Spring)

8,000# OIL BATH W/215/75R17.5 LR-H SINGLES(DEXTER)

- (2) Electric (Spring)(2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

TAIL OPTIONS

- Straight Deck w/ 6'6" Slide-in Ramps*
- 3' Dovetail w/ 5' Slide-in Ramps (18' and up)
- 3' Dovetail w/ 2, 16"x60" Foldup Ramps
- 3' Dovetail w/ 2, 31"x66"HD Foldup Ramps
- 4' Dove with 2 Flipover Ramps (20' and up)
- 4' Dove with 3 Flipover Ramps (20' and up)
- 4' Dove with 4ft. Monster Ramps (20' and up)
- 5' Dove with 2 Flipover Ramps (w/R opt.& 20' & up)

OTHER OPTIONS

- Add BlackWood Pro to Dovetail and Ramps
- Add BlackWood Pro to Dovetail
- Blackwood Pro Full Deck
- Blackwood Pro Outer Deck
- 1 Extra Pair Flushmount D-Rings on Steel Floor
- 1 Pair D-Rings
- Add 7-Way RV Plug to Rear Bumper

- Under Frame Fork Rack (96" Wide Only)
- 2 Hydraulic Monster Jacks™
- Light Bar w/4 Lights
- 1 Pair Weld-On Strap Ratchets
- 1 Side-mount Toolbox 30"x14"
- Under Frame Spare Tire and Mount
- Monster Steps on Both Sides
- Plate for Winch
- Full Size Toolbox (Bumper Pull)
- 12"oc Crossmembers
- Rough Oak Floor
- 2nd Jack
- Receiver Hitch
- 4" Ratchets every 4ft w/ Slide Track
- Mount Only for Spare Tire
- 11ga (1/8") DP Steel Floor w/ 4 D-Rings & 12"oc
- Front Toolbox (Bumper Pull)
- 102" Deck Width
- Spare Tire and Mount (Bumper Pull)
- Ramp Support Arms w/. Dove